


## Uponor RS adapter S-Press 63-RS2

**1029125**

- Made of tin-plated brass
- Fits to all RS2 or RS3 base parts.



### Application information Uponor RS adapter S-Press

#### Specification

- with fixed press sleeve
- stop ring
- colour code
- Test safety

#### Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

if not different mentioned:


- Male and female threads acc.to EN 10226-1.

#### Certification

- Approvals by local OM.
- E.g.
- DVGW
  - AENOR

## Uponor RS adapter S-Press 63-RS2

1029125



### Product code

Item no EAN	4021598106628
Item no GF	35001029125
Item no GTIN	04021598106628
Item no NRF	5071233
Item no VVS	045450063

### Dimensions

Item Unit Height	70
Item Unit Length	92
Item Unit Weight	0,57
Item Unit Width	70
Item_UOM	pce

### Measurements

LENGTH_L	87,8
Length (l1)	20
Length (l2)	60,7
z1	7,1

### Packaging

Packaging GTIN PL1	06414905263776
Packaging GTIN PL4	06414905263783
Packaging Height PL1	100
Packaging Height PL4	680
Packaging Length PL1	96
Packaging Length PL4	1200
Packaging Quantity PL1	1
Packaging Quantity PL4	400
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet

Packaging Volume PL1	0,0008832
Packaging Volume PL4	0,6528
Packaging Weight PL1	0,68
Packaging Weight PL4	252
Packaging Width PL1	92
Packaging Width PL4	800

## Documents

Page with all documents



### Uponor Corporation

Ilmalantori 4  
00240, Helsinki  
Finland

T +358 (0)20 129 211  
E  
communications@georgfischer.  
com