


## Uponor RS adapter female thread Rp1"FT-RS2

**1029134**

- Made of tin-plated brass.
- fits to all RS2 or RS3 base parts



### Application information Uponor RS adapter female thread

#### Specification

- with fixed press sleeve
- stop ring
- colour code
- Test safety

#### Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.


if not different mentioned:

- Male and female threads acc.to EN 10226-1.

#### Certification

- Approvals by local OM.
- E.g.
- DVGW
  - AENOR

Uponor RS adapter female thread Rp1"FT-RS2  
1029134



Technical data

Item (unit of measurement)	pce
Item no VVS	045452165
Item no LVI	1720829
Item no NRF	5071241
Female thread Rp	1 inch
Length (l)	45 mm
Length (l1)	20 mm
Length (l2)	19 mm
Packaging Quantity PL1	1
Packaging Quantity PL4	480

Documents

Page with all documents



Uponor Corporation

Ilmalantori 4  
00240, Helsinki  
Finland

T +358 (0)20 129 211  
E info@uponor.com  
F +358 (0)20 129 2841

www.uponor.com