


Uponor RS elbow RS2-RS2

1029138

- Made of tin-plated brass
- Base part for all RS2 or RS3 inserts including 2 lock pins.



Application information Uponor RS elbow

Specification

- with fixed press sleeve
- stop ring
- colour code
- Test safety

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

if not different mentioned:

- Male and female threads acc.to EN 10226-1.

Certification


- Approvals by local OM.

E.g.

- DVGW
- AENOR

Uponor RS elbow RS2-RS2

1029138



Technical data

Item (unit of measurement)	pce
Item no VVS	045453112
Item no LVI	1720811
Item no NRF	5071221
Length (l1)	51 mm
Length (l2)	51 mm
Packaging Quantity PL1	1
Packaging Quantity PL4	336

Documents

Page with all documents



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E info@uponor.com
F +358 (0)20 129 2841

www.uponor.com