


Uponor RS elbow 45deg RS2-RS2

1029140

- Made of tin-plated brass
- Base part for all RS2 or RS3 inserts including 2 lock pins.



Application information Uponor RS elbow 45deg

Specification

- with fixed press sleeve
- stop ring
- colour code
- Test safety

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

if not different mentioned:


- Male and female threads acc.to EN 10226-1.

Certification

- Approvals by local OM.
- E.g.
- DVGW
 - AENOR

Uponor RS elbow 45deg RS2-RS2

1029140



Technical data

Item (unit of measurement)	pce
Item no VVS	045454112
Item no LVI	1720813
Item no NRF	5071223
Length (l1)	51 mm
Length (l2)	51 mm
Packaging Quantity PL1	1
Packaging Quantity PL4	336

Documents

[Page with all documents](#)

Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E info@uponor.com
F +358 (0)20 129 2841

www.uponor.com