


Uponor Vario PLUS manifold w. valve LS 6x3/4 Euro

1030582

- with valve and eurocone thread



Application information Uponor Vario PLUS manifold w. valve

Specification

- Modular fibre glass reinforced polyamide manifold with 1,3,4,6 loops for connection with basic kit
- connection right or left with flat sealing or connection from below with optional elbowset
- supply with lockshield (LS) valve for balancing with adjusting ring or supply with Flowmeter (FM) for balancing
- shut-off and flow view
- adjusting ring for balancing without tools
- prepared places for room name labels
- return with valves and caps, prepared for actuators
- loop connection G3/4" eurocone
- loop pitch 50 mm
- header pitch 225 mm

Actuator:

- NC (normally closed) = closes without power

Application


- for underfloor heating and cooling
- can be combined with actuators MT 30x1,5

Certification

- CE

Uponor Vario PLUS manifold w. valve LS 6x3/4 Euro

1030582



Product code

Item no EAN	4016203841261
Item no GF	35001030582
Item no GTIN	04016203841261
Item no LVI	2025027
Item no NOBB	42496054
Item no NRF	8362716
Item no RSK	2418997
Item no VVS	087605136

Dimensions

Item Unit Height	180
Item Unit Length	320
Item Unit Weight	1,414
Item Unit Width	45
Item_UOM	pr

Packaging

Packaging GTIN PL1	06414905264988
Packaging GTIN PL4	06414905264995
Packaging Height PL1	137
Packaging Height PL4	1500
Packaging Length PL1	325
Packaging Length PL4	1200
Packaging Quantity PL1	1
Packaging Quantity PL4	155
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,003784625
Packaging Volume PL4	1,44

Packaging Weight PL1	1,464
Packaging Weight PL4	251,92
Packaging Width PL1	85
Packaging Width PL4	800

Documents

Page with all documents 

Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211

www.uponor.com