

Uponor Vario PLUS elbow connection 122/42

1032702

- Used when supply pipe comes from above/below
- Includes 2 different-length elbows for parallel arrangement



Application information Uponor Vario PLUS elbow connection

Specification

- Modular fibre glass reinforced polyamide manifold with 1,3,4,6 loops for connection with basic kit
- connection right or left with flat sealing or connection from below with optional elbowset
- supply with lockshield (LS) valve for balancing with adjusting ring or supply with Flowmeter (FM) for balancing
- shut-off and flow view
- adjusting ring for balancing without tools
- prepared places for room name labels
- return with valves and caps, prepared for actuators
- loop connection G3/4" eurocone
- loop pitch 50 mm
- header pitch 225 mm

Actuator:

- NC (normally closed) = closes without power

Application

- for underfloor heating and cooling
- can be combined with actuators MT 30x1,5

Certification

- CE

Uponor Vario PLUS elbow connection 122/42

1032702



Product code

Item no EAN	4016203841209
Item no GF	35001032702
Item no GTIN	04016203841209
Item no LVI	2026802
Item no NOBB	41947897
Item no NRF	8362653
Item no RSK	2418964
Item no VVS	087602150

Dimensions

Item Unit Height	40
Item Unit Length	125
Item Unit Weight	0,12
Item Unit Width	60
Item_UOM	pr

Measurements

Length (I1)	122
Length (I2)	43,5
Length (I3)	40,4

Packaging

Packaging GTIN PL1	06414905265084
Packaging GTIN PL3	06414905265091
Packaging GTIN PL4	06414905265107
Packaging Height PL1	50
Packaging Height PL3	90
Packaging Height PL4	1500
Packaging Length PL1	200
Packaging Length PL3	225

Packaging Length PL4	1200
Packaging Quantity PL1	1
Packaging Quantity PL3	5
Packaging Quantity PL4	720
Packaging Type PL1	Plastic_Bag
Packaging Type PL3	Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,003
Packaging Volume PL3	0,00374625
Packaging Volume PL4	1,44
Packaging Weight PL1	0,14
Packaging Weight PL3	0,75
Packaging Weight PL4	133
Packaging Width PL1	300
Packaging Width PL3	185
Packaging Width PL4	800

Documents

Page with all documents



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211

www.uponor.com