


Uponor S-Press elbow PPSU 63-63

1032877

- Fast installation with easy bevel and without calibration
- Colour code



Application information Uponor S-Press elbow PPSU

Specification

- with fixed press sleeve
- stop ring
- test safety

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

- if not different mentioned:


Male and female threads acc.to EN 10226-1.

Certification

- Approvals by local OM.
- E.g.
- DVGW
 - AENOR

Uponor S-Press elbow PPSU 63-63

1032877



Product code

Item no EAN	6414905220762
Item no GF	35001032877
Item no GTIN	06414905220762
Item no LVI	1720102
Item no NOBB	54938940
Item no NRF	5114358
Item no RSK	1896573
Item no VVS	087430163

Dimensions

Item Unit Height	72
Item Unit Length	139
Item Unit Weight	0,437
Item Unit Width	139
Item_UOM	pce

Measurements

Length (l1)	101,2
Length (l2)	101,2
z1	40,3
Z2	40,3

Packaging

Packaging GTIN PL1	06414905281107
Packaging GTIN PL4	06414905281114
Packaging Height PL1	105
Packaging Height PL4	756
Packaging Length PL1	160
Packaging Length PL4	1200
Packaging Quantity PL1	1

Packaging Quantity PL4	210
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,002688
Packaging Volume PL4	0,72576
Packaging Weight PL1	0,537
Packaging Weight PL4	137,77
Packaging Width PL1	160
Packaging Width PL4	800

Documents

Page with all documents 

Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211

www.uponor.com