


Uponor S-Press reducer PPSU 75-63

1032886

- Fast installation with easy bevel and without calibration
- Colour code



Application information Uponor S-Press reducer PPSU

Specification

- with fixed press sleeve
- stop ring
- test safety

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

- if not different mentioned:


Male and female threads acc.to EN 10226-1.

Certification

- Approvals by local OM.
- E.g.
- DVGW
 - AENOR

Uponor S-Press reducer PPSU 75-63

1032886



Product code

Item no EAN	6414905220854
Item no GF	35001032886
Item no GTIN	06414905220854
Item no LVI	1720152
Item no NOBB	54939038
Item no NRF	5114368
Item no RSK	1899465
Item no VVS	087455175

Dimensions

Item Unit Height	84
Item Unit Length	137
Item Unit Weight	0,418
Item Unit Width	84
Item_UOM	pce

Measurements

LENGTH_L	136,6
Length (l1)	60,5
Length (l2)	59
z1	16,7

Packaging

Packaging GTIN PL1	06414905281176
Packaging GTIN PL4	06414905281183
Packaging Height PL1	105
Packaging Height PL4	756
Packaging Length PL1	146
Packaging Length PL4	1200
Packaging Quantity PL1	1

Packaging Quantity PL4	384
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00142569
Packaging Volume PL4	0,72576
Packaging Weight PL1	0,465
Packaging Weight PL4	203,56
Packaging Width PL1	93
Packaging Width PL4	800

Documents

[Page with all documents](#)

Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211

www.uponor.com