


## Uponor S-Press tee reducer PPSU 75-50-75

**1032894**

- Fast installation with easy bevel and without calibration
- Colour code



### Application information Uponor S-Press tee reducer PPSU

#### Specification

- with fixed press sleeve
- stop ring
- test safety

#### Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

- if not different mentioned:


Male and female threads acc.to EN 10226-1.

#### Certification

- Approvals by local OM.
- E.g.
- DVGW
  - AENOR

## Uponor S-Press tee reducer PPSU 75-50-75

1032894



### Product code

Item no EAN	6414905220939
Item no GF	35001032894
Item no GTIN	06414905220939
Item no LVI	1720165
Item no NOBB	54939114
Item no NRF	5114377
Item no RSK	1808048
Item no VVS	087442172

### Dimensions

Item Unit Height	84
Item Unit Length	215
Item Unit Weight	0,752
Item Unit Width	129
Item_UOM	pce

### Measurements

Length (I1)	107,5
Length (I2)	85,6
Length (I3)	107,5
z1	46,6
Z2	48,6
Z3	46,6

### Packaging

Packaging GTIN PL1	06414905281411
Packaging GTIN PL4	06414905281428
Packaging Height PL1	105
Packaging Height PL4	756
Packaging Length PL1	224

Packaging Length PL4	1200
Packaging Quantity PL1	1
Packaging Quantity PL4	150
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,0037632
Packaging Volume PL4	0,72576
Packaging Weight PL1	0,872
Packaging Weight PL4	155,8
Packaging Width PL1	160
Packaging Width PL4	800

## Documents

Page with all documents



### Uponor Corporation

Ilmalantori 4  
00240, Helsinki  
Finland

T +358 (0)20 129 211  
E  
communications@georgfischer.  
com