

Uponor Ecoflex wall through sealing 175

1034203

- For concrete-cast and brick walls
- Prevents moisture from entering the building
- Applicable for NWP = no pressurized water area



Application information Uponor Ecoflex wall through sealing

Specification

- All accessories are corrosion resistant.

Application

- Ecoflex accessories are designed to complete the assortment in buried installation.

Certification

- Approvals should be checked by local responsible person

Uponor Ecoflex wall through sealing 175

1034203

**Measurements**

| | |
|-------------------|-----|
| Inner_diameter_di | 175 |
| LENGTH_L | 40 |
| Outer Diameter_do | 225 |

Product code

| | |
|--------------|----------------|
| Item no EAN | 7321500038601 |
| Item no GF | 35001034203 |
| Item no GTIN | 07321500038601 |
| Item no LVI | 3010648 |
| Item no NOBB | 41945555 |
| Item no NRF | 8360582 |
| Item no RSK | 4054776 |
| Item no VVS | 087916317 |

Dimensions

| | |
|------------------|------|
| Item Unit Height | 40 |
| Item Unit Length | 225 |
| Item Unit Weight | 0,43 |
| Item Unit Width | 225 |
| Item_UOM | pce |

Packaging

| | |
|------------------------|----------------|
| Packaging GTIN PL3 | 06414905266067 |
| Packaging Height PL3 | 260 |
| Packaging Length PL3 | 600 |
| Packaging Quantity PL3 | 30 |
| Packaging Type PL3 | Box |
| Packaging Volume PL3 | 0,0624 |
| Packaging Weight PL3 | 13,5 |
| Packaging Width PL3 | 400 |

Documents

Page with all documents



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E
communications@georgfischer.
com