

Uponor Ecoflex wall through sealing 175

1034203

- For concrete-cast and brick walls
- Prevents moisture from entering the building
- Applicable for NWP = no pressurized water area



Application information Uponor Ecoflex wall through sealing

Specification

- All accessories are corrosion resistant.

Application

- Ecoflex accessories are designed to complete the assortment in buried installation.

Certification

- Approvals should be checked by local responsible person

Uponor Ecoflex wall through sealing 175

1034203

**Measurements**

Inner_diameter_di	175
LENGTH_L	40
Outer Diameter_do	225

Product code

Item no EAN	7321500038601
Item no GF	35001034203
Item no GTIN	07321500038601
Item no LVI	3010648
Item no NOBB	41945555
Item no NRF	8360582
Item no RSK	4054776
Item no VVS	087916317

Dimensions

Item Unit Height	40
Item Unit Length	225
Item Unit Weight	0,43
Item Unit Width	225
Item_UOM	pce

Packaging

Packaging GTIN PL3	06414905266067
Packaging Height PL3	260
Packaging Length PL3	600
Packaging Quantity PL3	30
Packaging Type PL3	Box
Packaging Volume PL3	0,0624
Packaging Weight PL3	13,5
Packaging Width PL3	400

Documents

Page with all documents



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211

www.uponor.com