

## Uponor Ecoflex wall through sealing 200

**1034204**

- For concrete-cast and brick walls
- Prevents moisture from entering the building
- Applicable for NWP = no pressurized water area



### Application information Uponor Ecoflex wall through sealing

#### Specification

- All accessories are corrosion resistant.

#### Application

- Ecoflex accessories are designed to complete the assortment in buried installation.

#### Certification

- Approvals should be checked by local responsible person

## Uponor Ecoflex wall through sealing 200

1034204



### Measurements

Inner_diameter_di	200
LENGTH_L	50
Outer Diameter_do	250

### Product code

Item no EAN	7321500027896
Item no GF	35001034204
Item no GTIN	07321500027896
Item no LVI	3010646
Item no NOBB	41945566
Item no NRF	8360583
Item no RSK	4054777
Item no VVS	087916420

### Dimensions

Item Unit Height	50
Item Unit Length	250
Item Unit Weight	0,620
Item Unit Width	250
Item_UOM	pce

### Packaging

Packaging GTIN PL3	06414905266081
Packaging Height PL3	260
Packaging Length PL3	600
Packaging Quantity PL3	20
Packaging Type PL3	Box
Packaging Volume PL3	0,0624
Packaging Weight PL3	13
Packaging Width PL3	400

## Documents

Page with all documents



### Uponor Corporation

Ilmalantori 4  
00240, Helsinki  
Finland

T +358 (0)20 129 211

[www.uponor.com](http://www.uponor.com)