


Uponor S-Press PLUS coupling PPSU 16-16

1039933

- Material: PPSU



Application information Uponor S-Press PLUS coupling PPSU

Specification

- Unique press indicator
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access
- Colour code
- Fixed press sleeve with inspection window
- Precise jaw fixation
- Fast diameter recognition
- Accurate test safety function
- 100% backward compatible with existing Uponor components
- Flow rate optimized fitting body

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

if not different mentioned:

- Male and female threads acc.to EN 10226-1.

Certification


- Approvals by local OM.

E.g.

- DVGW
- AENOR

Uponor S-Press PLUS coupling PPSU 16-16

1039933



Product code

Item no EAN	6414905228720
Item no GF	35001039933
Item no GTIN	06414905228720
Item no LVI	1720690
Item no NOBB	55171495
Item no NRF	5114385
Item no RSK	1899399
Item no VVS	087452116

Dimensions

Item Unit Height	21.9
Item Unit Length	50.5
Item Unit Weight	0,01532
Item Unit Width	21.9
Item_UOM	pce

Measurements

LENGTH_L	50,5
Length (l1)	19,9
Length (l2)	19,9
z1	10,7

Packaging

Packaging GTIN PL1	06414905634880
Packaging GTIN PL3	06414905425525
Packaging GTIN PL4	06414905287000
Packaging Height PL1	89
Packaging Height PL3	95
Packaging Height PL4	714
Packaging Length PL1	176

Packaging Length PL3	277
Packaging Length PL4	1200
Packaging Quantity PL1	20
Packaging Quantity PL3	80
Packaging Quantity PL4	7680
Packaging Type PL1	Base_Box
Packaging Type PL3	Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,001049488
Packaging Volume PL3	0,004710385
Packaging Volume PL4	0,68544
Packaging Weight PL1	0,338
Packaging Weight PL3	1,552
Packaging Weight PL4	173,992
Packaging Width PL1	67
Packaging Width PL3	179
Packaging Width PL4	800

Documents

Page with all documents



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211

www.uponor.com