


Uponor S-Press PLUS coupling PPSU 25-25

1039935

- Material: PPSU



Application information Uponor S-Press PLUS coupling PPSU

Specification

- Unique press indicator
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access
- Colour code
- Fixed press sleeve with inspection window
- Precise jaw fixation
- Fast diameter recognition
- Accurate test safety function
- 100% backward compatible with existing Uponor components
- Flow rate optimized fitting body

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

if not different mentioned:

- Male and female threads acc.to EN 10226-1.

Certification


- Approvals by local OM.

E.g.

- DVGW
- AENOR

Uponor S-Press PLUS coupling PPSU 25-25

1039935



Product code

Item no EAN	6414905228744
Item no GF	35001039935
Item no GTIN	06414905228744
Item no LVI	1720692
Item no NOBB	55171514
Item no NRF	5114387
Item no RSK	1899401
Item no VVS	087452125

Dimensions

Item Unit Height	32.2
Item Unit Length	68
Item Unit Weight	0,04928
Item Unit Width	32.2
Item_UOM	pce

Measurements

LENGTH_L	68
Length (l1)	28,3
Length (l2)	28,3
z1	11,4

Packaging

Packaging GTIN PL1	06414905635115
Packaging GTIN PL3	06414905635122
Packaging GTIN PL4	06414905641321
Packaging Height PL1	89
Packaging Height PL3	189
Packaging Height PL4	711
Packaging Length PL1	176

Packaging Length PL3	357
Packaging Length PL4	1200
Packaging Quantity PL1	10
Packaging Quantity PL3	80
Packaging Quantity PL4	1920
Packaging Type PL1	Base_Box
Packaging Type PL3	Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00211464
Packaging Volume PL3	0,018555075
Packaging Volume PL4	0,68256
Packaging Weight PL1	0,564
Packaging Weight PL3	5,032
Packaging Weight PL4	266,536
Packaging Width PL1	135
Packaging Width PL3	275
Packaging Width PL4	800

Documents

Page with all documents



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211

www.uponor.com