


## Uponor S-Press PLUS reducer PPSU 25-20

**1039939**

- Material: PPSU



### Application information Uponor S-Press PLUS reducer PPSU

#### Specification

- Unique press indicator
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access
- Colour code
- Fixed press sleeve with inspection window
- Precise jaw fixation
- Fast diameter recognition
- Accurate test safety function
- 100% backward compatible with existing Uponor components
- Flow rate optimized fitting body

#### Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

if not different mentioned:

- Male and female threads acc.to EN 10226-1.

#### Certification


- Approvals by local OM.

E.g.

- DVGW
- AENOR

## Uponor S-Press PLUS reducer PPSU 25-20

1039939



### Product code

Item no EAN	6414905229352
Item no GF	35001039939
Item no GTIN	06414905229352
Item no LVI	1720696
Item no NOBB	55171552
Item no NRF	5114392
Item no RSK	1899405
Item no VVS	087454125

### Dimensions

Item Unit Height	32.2
Item Unit Length	61
Item Unit Weight	0,03745
Item Unit Width	32.2
Item_UOM	pce

### Measurements

LENGTH_L	61
Length (l1)	28,3
Length (l2)	21,3
z1	11,4

### Packaging

Packaging GTIN PL1	06414905635177
Packaging GTIN PL3	06414905635184
Packaging GTIN PL4	06414905477876
Packaging Height PL1	89
Packaging Height PL3	188
Packaging Height PL4	708
Packaging Length PL1	176

Packaging Length PL3	277
Packaging Length PL4	1200
Packaging Quantity PL1	10
Packaging Quantity PL3	80
Packaging Quantity PL4	3840
Packaging Type PL1	Base_Box
Packaging Type PL3	Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,001049488
Packaging Volume PL3	0,009321604
Packaging Volume PL4	0,67968
Packaging Weight PL1	0,408
Packaging Weight PL3	3,664
Packaging Weight PL4	200,872
Packaging Width PL1	67
Packaging Width PL3	179
Packaging Width PL4	800

## Documents

Page with all documents



### Uponor Corporation

Ilmalantori 4  
00240, Helsinki  
Finland

T +358 (0)20 129 211

[www.uponor.com](http://www.uponor.com)