
Product data sheet




GF Uponor S-Press PLUS tee reducer PPSU 25-16-25

1039955

- Material: PPSU
- Fixed stainless steel sleeve





Application information GF Uponor S-Press PLUS tee reducer PPSU

Specification

- Unique press indicator
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access
- Colour code
- Fixed press sleeve with insprection window
- Precise jaw fixation
- Fast diameter recognition
- Accurate test safety function
- 100% backward compatible with existing Uponor components
- Flow rate optimized fitting body

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

if not different mentioned:
- Male and female threads acc.to EN 10226-1.


Certification

- Approvals by local OM.

E.g.
- DVGW
- AENOR

GF Uponor S-Press PLUS tee reducer PPSU 25-16-25

1039955



Product code

Item no EAN	6414905228935
Item no GF	35001039955
Item no GTIN	06414905228935
Item no LVI	1720712
Item no NOBB	55171684
Item no NRF	5114409
Item no RSK	1807991
Item no VVS	087444125

Dimensions

Item Unit Height	55.1
Item Unit Length	95
Item Unit Weight	0,068
Item Unit Width	32.2
Item_UOM	pce

Measurements

Length (l1)	47,5
Length (l2)	39
Length (l3)	47,5
z1	19,2
Z2	19,1
Z3	19,2

Packaging

Packaging GTIN PL1	06414905635252
Packaging GTIN PL3	06414905635429
Packaging GTIN PL4	06414905479962

Packaging Height PL1	89
Packaging Height PL3	189
Packaging Height PL4	711
Packaging Length PL1	176
Packaging Length PL3	357
Packaging Length PL4	1200
Packaging Quantity PL1	10
Packaging Quantity PL3	80
Packaging Quantity PL4	1920
Packaging Type PL1	Base_Box
Packaging Type PL3	Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00211464
Packaging Volume PL3	0,018555075
Packaging Volume PL4	0,68256
Packaging Weight PL1	0,754
Packaging Weight PL3	6,552
Packaging Weight PL4	182,248
Packaging Width PL1	135
Packaging Width PL3	275
Packaging Width PL4	800

Documents

Page with all documents

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E communications@georgfischer.com

www.uponor.com

+GF+