

## Uponor RS lock pin RS3 grey

**1042922**

- made of plastic
- to lock the RS insert to the RS base part.



### Application information Uponor RS lock pin

#### Specification

- with fixed press sleeve
- stop ring
- colour code
- Test safety

#### Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

if not different mentioned:

- Male and female threads acc.to EN 10226-1.

#### Certification

- Approvals by local OM.

E.g.

- DVGW
- AENOR

## Uponor RS lock pin RS3 grey

1042922



### Product code

Item no EAN	4021598106864
Item no GF	35001042922
Item no GTIN	04021598106864
Item no LVI	1720627
Item no NRF	5079073
Item no RSK	1877272
Item no VVS	045459122

### Dimensions

Item Unit Height	8
Item Unit Length	280
Item Unit Weight	0,004
Item Unit Width	8
Item_UOM	pce

### Packaging

Packaging GTIN PL1	06414905458851
Packaging Height PL1	15
Packaging Length PL1	320
Packaging Material (number) PL1	4
Packaging Material PL1	Low density polyethylene
Packaging Material (short) PL1	LDPE
Packaging Quantity PL1	10
Packaging Type PL1	Plastic_Bag
Packaging Volume PL1	0,00096
Packaging Weight PL1	0,06
Packaging Width PL1	200

### Technical data

Recycling Text Block PL1	Low density polyethylene
--------------------------	--------------------------

## Documents

Page with all documents



### Uponor Corporation

Ilmalantori 4  
00240, Helsinki  
Finland

T +358 (0)20 129 211

[www.uponor.com](http://www.uponor.com)