

Uponor RS lock pin RS3 grey

1042922

- made of plastic
- to lock the RS insert to the RS base part.



Application information Uponor RS lock pin

Specification

- with fixed press sleeve
- stop ring
- colour code
- Test safety

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

if not different mentioned:

- Male and female threads acc.to EN 10226-1.

Certification

- Approvals by local OM.

E.g.

- DVGW
- AENOR

Uponor RS lock pin RS3 grey

1042922



Product code

Item no EAN	4021598106864
Item no GF	35001042922
Item no GTIN	04021598106864
Item no LVI	1720627
Item no NRF	5079073
Item no RSK	1877272
Item no VVS	045459122

Dimensions

Item Unit Height	8
Item Unit Length	280
Item Unit Weight	0,004
Item Unit Width	8
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905458851
Packaging Height PL1	15
Packaging Length PL1	320
Packaging Material (number) PL1	4
Packaging Material PL1	Low density polyethylene
Packaging Material (short) PL1	LDPE
Packaging Quantity PL1	10
Packaging Type PL1	Plastic_Bag
Packaging Volume PL1	0,00096
Packaging Weight PL1	0,06
Packaging Width PL1	200

Technical data

Recycling Text Block PL1	Low density polyethylene
--------------------------	--------------------------

Documents

Page with all documents



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E
communications@georgfischer.
com