


## Uponor Ecoflex Thermo single PN10 63x8,6/175

1045879

- Heating and Cooling
- One medium pipe PE-Xa with oxygen barrier, SDR 7,4
- Max. load 10 bar / 95°C
- PEX foam, HDPE casing
- Production in Russia / Make to order / Please ask about delivery time



### Application information Uponor Ecoflex Thermo single PN10

#### Specification

- Flexible, pre-insulated, self-compensating plastic pipe system produced based on EN 15632
- Medium pipe: cross-linked polyethylene (PE-Xa) pipe based on EN ISO 15875, natural coloured, PN 6 (SDR 11) or PN 10 (SDR 7,4), Oxygen tightness based on EN 15632
- Insulating material: closed-cell PE-X foam, permanently elastic, ageing-resistant
- Casing pipe: Corrugated polyethylene (HDPE)

#### Application


- Transport of heating and cooling water for buried installations.
- Heating operating temperature 80°C based on EN 15632
- Malfunction temperature 95°C
- Static verification for heavy traffic load of 60 tons

#### Certification

- Approvals should be checked by local responsible person

Uponor Ecoflex Thermo single PN10 63x8,6/175

1045879



Technical data

Item (unit of measurement)	m
Item no VVS	087806163
Bending radius 2	0,65 m
Packaging Quantity PL1	200

Documents

Page with all documents 

Uponor Corporation

Ilmalantori 4  
00240, Helsinki  
Finland

T +358 (0)20 129 211  
E info@uponor.com  
F +358 (0)20 129 2841

www.uponor.com