Product data sheet



GF Uponor Sport tichelmann manifold Q&E 3x25

1046748

- 6 Q&E rings 25
- 2 Q&E rings 40





Application information GF Uponor Sport tichelmann manifold Q&E

Specification

- Sprung floor heating system, for installation between joists of sprung-floor constructions for sports.
- for installations with pipe c-c 100mm
- for pipe dim 25mm

- Sport tichelmann manifold
- Material: Uponor eval PE-Xa pipes + Uponor PPSU fittings

Application

- radiant underfloor heating
- for sports floors
- for connection of Uponor PE-Xa pipes 25x2.3mm with Uponor Q&E connection technology for sportsfloor
- for the use in sportsfloor UFH systems according to theTichelmann principle

Certification

- DIN CERTCO: 7F134-F, 7F465-F, 7F466-F

GF Uponor Sport tichelmann manifold Q&E 3x25

1046748





Product code

Item no EAN	4021598113558
Item no GF	35001046748
Item no GTIN	04021598113558

Dimensions

Item Unit Height	70
Item Unit Length	2110
Item Unit Weight	3,35
Item Unit Width	200
Item_UOM	set

Packaging

Packaging GTIN PL1	06414905460458
Packaging Height PL1	100
Packaging Length PL1	2100
Packaging Quantity PL1	1
Packaging Type PL1	Base_Box
Packaging Volume PL1	0,0315
Packaging Weight PL1	3,45
Packaging Width PL1	150

Documents

Page with all documents

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E communications@georgfischer.com

www.uponor.com

+GF+