

## Uponor Vario PLUS overflow valve 225mm

**1046884**

- Adjustable difference pressure regulation



### Application information Uponor Vario PLUS overflow valve

#### Specification

- Modular fibre glass reinforced polyamide manifold with 1,3,4,6 loops for connection with basic kit
- connection right or left with flat sealing or connection from below with optional elbowset
- supply with lockshield (LS) valve for balancing with adjusting ring or supply with Flowmeter (FM) for balancing
- shut-off and flow view
- adjusting ring for balancing without tools
- prepared places for room name labels
- return with valves and caps, prepared for actuators
- loop connection G3/4" eurocone
- loop pitch 50 mm
- header pitch 225 mm

Actuator:

- NC (normally closed) = closes without power

#### Application

- for underfloor heating and cooling
- can be combined with actuators MT 30x1,5

#### Certification

- CE

## Uponor Vario PLUS overflow valve 225mm

1046884



### Product code

Item no EAN	4021598113282
Item no GF	35001046884
Item no GTIN	04021598113282

### Dimensions

Item Unit Height	30
Item Unit Length	120
Item Unit Weight	0,177
Item Unit Width	70
Item_UOM	pce

### Packaging

Packaging GTIN PL1	06414905401406
Packaging GTIN PL4	06414905656004
Packaging Height PL1	135
Packaging Height PL4	1500
Packaging Length PL1	132
Packaging Length PL4	1200
Packaging Quantity PL1	1
Packaging Quantity PL4	640
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,0008019
Packaging Volume PL4	1,44
Packaging Weight PL1	0,227
Packaging Weight PL4	170,28
Packaging Width PL1	45
Packaging Width PL4	800

## Documents

Page with all documents



### Uponor Corporation

Ilmalantori 4  
00240, Helsinki  
Finland

T +358 (0)20 129 211

[www.uponor.com](http://www.uponor.com)