

Uponor Vario PLUS overflow valve 225mm

1046884

- Adjustable difference pressure regulation



Application information Uponor Vario PLUS overflow valve

Specification

- Modular fibre glass reinforced polyamide manifold with 1,3,4,6 loops for connection with basic kit
- Connection right or left with flat sealing or connection from below with optional elbowset
- Supply with lockshield (LS) valve for balancing with adjusting ring or supply with Flowmeter (FM) for balancing
- Shut-off and flow view
- Adjusting ring for balancing without tools
- Prepared places for room name labels
- Return with valves and caps, prepared for actuators
- Loop connection G3/4" eurocone
- Loop pitch 50 mm
- Header pitch 225 mm

Actuator:

- NC (normally closed) = closes without power

Application

- For underfloor heating and cooling
- Can be combined with actuators MT 30x1,5

Certification

- CE

Uponor Vario PLUS overflow valve 225mm

1046884



Product code

Item no EAN	4021598113282
Item no GF	35001046884
Item no GTIN	04021598113282

Dimensions

Item Unit Height	30
Item Unit Length	120
Item Unit Weight	0,177
Item Unit Width	70
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905401406
Packaging GTIN PL4	06414905656004
Packaging Height PL1	135
Packaging Height PL4	1500
Packaging Length PL1	132
Packaging Length PL4	1200
Packaging Quantity PL1	1
Packaging Quantity PL4	640
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,0008019
Packaging Volume PL4	1,44
Packaging Weight PL1	0,227
Packaging Weight PL4	170,28
Packaging Width PL1	45
Packaging Width PL4	800

Documents

Page with all documents



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211

www.uponor.com