


## Uponor S-Press elbow 40-40

1046908

- Made of tin-plated brass
- Fast installation with easy bevel and without calibration
- Colour code



### Application information Uponor S-Press elbow

#### Specification

- with fixed press sleeve
- stop ring
- test safety

#### Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

- if not different mentioned:



Male and female threads acc.to EN 10226-1.

#### Certification

- Approvals by local OM.  
E.g.
  - DVGW
  - AENOR

## Uponor S-Press elbow 40-40

1046908



### Product code

Item no EAN	4021598114050
Item no GF	35001046908
Item no GTIN	04021598114050
Item no VVS	045470140

### Dimensions

Item Unit Height	42
Item Unit Length	87
Item Unit Weight	0,476
Item Unit Width	90
Item_UOM	pce

### Measurements

Length (l1)	71,5
Length (l2)	71,5
z1	33,6
z2	33,6

### Packaging

Packaging GTIN PL1	06414905401550
Packaging GTIN PL4	06414905401567
Packaging Height PL1	110
Packaging Height PL4	800
Packaging Length PL1	180
Packaging Length PL4	1200
Packaging Quantity PL1	5
Packaging Quantity PL4	600
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,0039996

Packaging Volume PL4	0,768
Packaging Weight PL1	2,43
Packaging Weight PL4	313,456
Packaging Width PL1	202
Packaging Width PL4	800

## Documents

Page with all documents 

### Uponor Corporation

Ilmalantori 4  
00240, Helsinki  
Finland

T +358 (0)20 129 211

[www.uponor.com](http://www.uponor.com)