


## Uponor S-Press elbow male thread 40-R1 1/4"MT

1046909

- Made of tin-plated brass
- Fast installation with easy bevel and without calibration
- Colour code



### Application information Uponor S-Press elbow male thread

#### Specification

- with fixed press sleeve
- stop ring
- test safety

#### Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

- if not different mentioned:


Male and female threads acc.to EN 10226-1.

#### Certification

- Approvals by local OM.  
E.g.
  - DVGW
  - AENOR

## Uponor S-Press elbow male thread 40-R1 1/4"MT

1046909



### Product code

Item no EAN	4021598114067
Item no GF	35001046909
Item no GTIN	04021598114067
Item no VVS	045471420

### Dimensions

Item Unit Height	60
Item Unit Length	85
Item Unit Weight	0,42
Item Unit Width	42
Item_UOM	pce

### Measurements

Length (l1)	49
Length (l2)	72
Male_thread_R	1 1/4
z1	30,3
Z2	34,1

### Packaging

Packaging GTIN PL1	06414905460540
Packaging GTIN PL4	06414905555260
Packaging Height PL1	105
Packaging Height PL4	645
Packaging Length PL1	176
Packaging Length PL4	800
Packaging Quantity PL1	5
Packaging Quantity PL4	500
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet

Packaging Volume PL1	0,00373296
Packaging Volume PL4	0,6192
Packaging Weight PL1	2,225
Packaging Weight PL4	242,5
Packaging Width PL1	202
Packaging Width PL4	1200

## Documents

Page with all documents



### Uponor Corporation

Ilmalantori 4  
00240, Helsinki  
Finland

T +358 (0)20 129 211  
E  
communications@georgfischer.  
com