

## Uponor S-Press reducer 40-32

**1046931**

- Made of tin-plated brass
- Fast installation with easy bevel and without calibration
- Colour code



### Application information Uponor S-Press reducer

#### Specification

- with fixed press sleeve
- stop ring
- test safety

#### Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

- if not different mentioned:

Male and female threads acc.to EN 10226-1.

#### Certification

- Approvals by local OM.
- E.g.
- DVGW
  - AENOR

## Uponor S-Press reducer 40-32

1046931



### Status

Item Available Till date 2026-12-31T00:00:00.000+0100

### Product code

Item no EAN	4021598114289
Item no GF	35001046931
Item no GTIN	04021598114289
Item no VVS	045480420

### Dimensions

Item Unit Height	47
Item Unit Length	85
Item Unit Weight	0,217
Item Unit Width	47
Item_UOM	pce

### Measurements

LENGTH_L	81,2
Length (l1)	37,9
Length (l2)	30,3
z1	13

### Packaging

Packaging GTIN PL1	06414905460717
Packaging GTIN PL4	06414905493524
Packaging Height PL1	89
Packaging Height PL4	570
Packaging Length PL1	135
Packaging Length PL4	1120
Packaging Quantity PL1	5
Packaging Quantity PL4	960
Packaging Type PL1	Base_Box

Packaging Type PL4	Pallet
Packaging Volume PL1	0,001045305
Packaging Volume PL4	0,4775232
Packaging Weight PL1	1,151
Packaging Weight PL4	222,432
Packaging Width PL1	87
Packaging Width PL4	748

## Documents

Page with all documents 

### Uponor Corporation

Ilmalantori 4  
00240, Helsinki  
Finland

T +358 (0)20 129 211

[www.uponor.com](http://www.uponor.com)