

Uponor S-Press reducer 50-32

1046933

- Made of tin-plated brass
- Fast installation with easy bevel and without calibration
- Colour code



Application information Uponor S-Press reducer

Specification

- with fixed press sleeve
- stop ring
- test safety

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

- if not different mentioned:

Male and female threads acc.to EN 10226-1.

Certification

- Approvals by local OM.
- E.g.
- DVGW
 - AENOR

Uponor S-Press reducer 50-32

1046933



Status

Item Available Till date

2026-12-31T00:00:00.000+0100

Product code

Item no EAN	4021598114302
Item no GF	35001046933
Item no GTIN	04021598114302
Item no VVS	045480440

Dimensions

Item Unit Height	68
Item Unit Length	82
Item Unit Weight	0,273
Item Unit Width	68
Item_UOM	pce

Measurements

LENGTH_L	81,2
Length (l1)	37,9
Length (l2)	30,3
z1	13

Packaging

Packaging GTIN PL1	06414905460724
Packaging GTIN PL4	06414905493531
Packaging Height PL1	90
Packaging Height PL4	570
Packaging Length PL1	70
Packaging Length PL4	1120
Packaging Quantity PL1	3
Packaging Quantity PL4	1152
Packaging Type PL1	Base_Box

Packaging Type PL4	Pallet
Packaging Volume PL1	0,0011025
Packaging Volume PL4	0,4775232
Packaging Weight PL1	0,86
Packaging Weight PL4	330,202
Packaging Width PL1	175
Packaging Width PL4	748

Documents

Page with all documents 

Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211

www.uponor.com