


Uponor RS adapter S-Press 40-RS2

1046940

- Made of tin-plated brass
- Fits to all RS2 or RS3 base parts.



Application information Uponor RS adapter S-Press

Specification

- with fixed press sleeve
- stop ring
- colour code
- Test safety

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

if not different mentioned:

- Male and female threads acc.to EN 10226-1.

Certification


- Approvals by local OM.

E.g.

- DVGW
- AENOR

Uponor RS adapter S-Press 40-RS2

1046940



Technical data

Item (unit of measurement) pce

Item no VVS 045450040

Item no NRF 5071231

Length (l) 65 mm

Length (l1) 20 mm

Length (l2) 38 mm

Packaging Quantity PL1 1

Packaging Quantity PL4 480

Documents

Page with all documents 

Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E info@uponor.com
F +358 (0)20 129 2841

www.uponor.com