

## Uponor Vario ball valve NP G1-G1

1059132

- Made of brass nickel-plated
- For flat sealing vertical connection G1
- 60 mm + length of the manifold



### Application information Uponor Vario ball valve

#### Specification

- Components made of brass, nickel-plated brass, steel, and engineered plastics
- Eurocone, threaded, and flat-sealing connections
- Compatible with Vario B, C, S, M, PLUS, and MAGNA manifolds
- Includes valves, flowmeters, air vents, actuators, and adapters
- Designed for heating and cooling applications

#### Application

- Completion and extension of Vario manifold installations
- Flow regulation, balancing, and shut-off
- Connection of PEX, MLCP, and composite pipes
- Integration of actuators, sensors, and control units
- Commissioning, maintenance, and system optimization

## Uponor Vario ball valve NP G1-G1

1059132



## Measurements

Cylindric_thread_G	1
Cylindric_thread_G1	1
LENGTH_L	70
Length (l1)	12
Length (l2)	12
Z Measurement h	51
z1	46

## Product code

Item no EAN	4021598120549
Item no GF	35001059132
Item no GTIN	04021598120549
Item no LVI	2024328
Item no NRF	8361113
Item no RSK	2987944
Item no VVS	087603108

## Dimensions

Item Unit Height	35
Item Unit Length	70
Item Unit Weight	0,95
Item Unit Width	35
Item_UOM	set

## Packaging

Packaging GTIN PL1	06414905474905
Packaging GTIN PL3	06414905474912
Packaging GTIN PL4	06414905474929
Packaging Height PL1	44
Packaging Height PL3	100

Packaging Height PL4	1500
Packaging Length PL1	144
Packaging Length PL3	390
Packaging Length PL4	1200
Packaging Quantity PL1	1
Packaging Quantity PL3	10
Packaging Quantity PL4	1050
Packaging Type PL1	Base_Box
Packaging Type PL3	Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,000462528
Packaging Volume PL3	0,006045
Packaging Volume PL4	1,44
Packaging Weight PL1	1
Packaging Weight PL3	10,05
Packaging Weight PL4	1080,25
Packaging Width PL1	73
Packaging Width PL3	155
Packaging Width PL4	800

## Documents

Page with all documents



### Uponor Corporation

Ilmalantori 4  
00240, Helsinki  
Finland

T +358 (0)20 129 211

[www.uponor.com](http://www.uponor.com)