


## Uponor RS adapter S-Press 16-RS2

**1059397**

- Made of tin-plated brass
- Fits to all RS2 base parts.



### Application information Uponor RS adapter S-Press

#### Specification

- with fixed press sleeve
- stop ring
- colour code
- Test safety

#### Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

if not different mentioned:


- Male and female threads acc.to EN 10226-1.

#### Certification

- Approvals by local OM.
- E.g.
- DVGW
  - AENOR

## Uponor RS adapter S-Press 16-RS2

1059397



### Product code

Item no EAN	4021598121690
Item no GF	35001059397
Item no GTIN	04021598121690
Item no RSK	1897882
Item no VVS	045450016

### Dimensions

Item Unit Height	68
Item Unit Length	58
Item Unit Weight	0,353
Item Unit Width	68
Item_UOM	pce

### Measurements

LENGTH_L	60,8
Length (l1)	20
Length (l2)	21
z1	19,8

### Packaging

Packaging GTIN PL1	06414905463534
Packaging GTIN PL4	06414905495702
Packaging Height PL1	78
Packaging Height PL4	800
Packaging Length PL1	118
Packaging Length PL4	1200
Packaging Quantity PL1	1
Packaging Quantity PL4	480
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet

Packaging Volume PL1	0,000901992
Packaging Volume PL4	0,768
Packaging Weight PL1	0,414
Packaging Weight PL4	194,44
Packaging Width PL1	98
Packaging Width PL4	800

## Documents

Page with all documents



### Uponor Corporation

Ilmalantori 4  
00240, Helsinki  
Finland

T +358 (0)20 129 211

[www.uponor.com](http://www.uponor.com)