
Product data sheet



GF Uponor Uni Pipe PLUS white S 32x3,0 5m

1059575

- bar
- High dimensional stability, low expansion rates
- Increased flexibility
- 100% oxygen barrier



Application information GF Uponor Uni Pipe PLUS white S

Specification

- Oxygen diffusion resistant multi-layer composite pipe (PE-RT - adhesive – seamless aluminium/longitudinally welded aluminium - adhesive - PE-RT) produced using SACP and OWC-technology.
- Fire classification E according to EN 13501-1.
- With pipe end caps as hygienic seal according EN 806.

Application

- Tested/Approved according EN ISO 21003 Multilayer piping systems for hot and cold water installations inside buildings for application class 1,2,4,5/10bar
- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

Certification


- Approvals by local OM.

E.g.

- DVGW
- AENOR

GF Uponor Uni Pipe PLUS white S 32x3,0 5m

1059575



Product code

Item no EAN	4021598121232
Item no GF	35001059575
Item no GTIN	04021598121232
Item no LVI	1720136
Item no NOBB	48165653
Item no NRF	5072101
Item no RSK	2004936
Item no VVS	087480132

Dimensions

Item Unit Height	32
Item Unit Length	1000
Item Unit Weight	0,413
Item Unit Width	32
Item_UOM	m

Measurements

Length	5
Outer Diameter_do	32
Wall thickness_s	3

Packaging

Packaging GTIN PL1	06414905412051
Packaging GTIN PL2	06414905412068
Packaging GTIN PL4	06414905412075
Packaging Height PL1	32
Packaging Height PL2	110
Packaging Height PL4	725

Packaging Length PL1	5000
Packaging Length PL2	5070
Packaging Length PL4	5080
Packaging Quantity PL1	5
Packaging Quantity PL2	35
Packaging Quantity PL4	1785
Packaging Type PL1	Piece
Packaging Type PL2	Cover_Pipe
Packaging Type PL4	Wooden_Cage
Packaging Volume PL1	0,00512
Packaging Volume PL2	0,061347
Packaging Volume PL4	4,23545
Packaging Weight PL1	2,066
Packaging Weight PL2	18,666
Packaging Weight PL4	951,941
Packaging Width PL1	32
Packaging Width PL2	110
Packaging Width PL4	1150

Documents

Page with all documents

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E communications@georgfischer.com

www.uponor.com

+GF+