



## Uponor Wipex adapter S-Press PN6 32x2,9-32x3,0

**1060058**

- Connection of PE-Xa pipe to Uponor MLC pipe.
- 6 bar
- DR = dezincification resistance brass



### Application information Uponor Wipex adapter S-Press PN6

#### Specification

- Wipex fittings in corrosion-resistant brass, dezincification based on EN ISO 6509 with stainless steel screw.
- O-ring sealing between Wipex coupling and base fitting connectors
- Bolt set for couplers include a hex socket bolt in stainless steel and the nut as well as washer from brass
- Pre-open sleeve design with assembled support part for the dimension 63-110mm.

#### Application


- Fittings for pipe systems Thermo, Aqua, Quattro, Supra, Supra PLUS and Supra Standard
- Connection of PE and PE-Xa medium pipe to couplers with cylindrical inch male thread
- Max. operating temperature 95°C

#### Certification

- Approvals should be checked by local responsible person

## Uponor Wipex adapter S-Press PN6 32x2,9-32x3,0

1060058



### Status

Item Available Till date

2026-12-31T00:00:00.000+0100

### Product code

Item no EAN	4021598121669
Item no GF	35001060058
Item no GTIN	04021598121669

### Dimensions

Item Unit Height	45
Item Unit Length	48
Item Unit Weight	0,244
Item Unit Width	65
Item_UOM	pce

### Measurements

LENGTH_L	66
Length (l1)	30
Length (l2)	26
z1	10

### Packaging

Packaging GTIN PL1	06414905412389
Packaging GTIN PL3	06414905412396
Packaging Height PL1	48
Packaging Height PL3	145
Packaging Length PL1	51
Packaging Length PL3	268
Packaging Quantity PL1	1
Packaging Quantity PL3	25
Packaging Type PL1	Plastic_Bag
Packaging Type PL3	Box

Packaging Volume PL1	0,000166464
Packaging Volume PL3	0,009715
Packaging Weight PL1	0,253
Packaging Weight PL3	6,28
Packaging Width PL1	68
Packaging Width PL3	250

## Documents

Page with all documents



### Uponor Corporation

Ilmalantori 4  
00240, Helsinki  
Finland

T +358 (0)20 129 211

[www.uponor.com](http://www.uponor.com)