



Uponor Wipex adapter S-Press PN6 40x3,7-40x4,0

1060059

- Connection of PE-Xa pipe to Uponor MLC pipe.
- 6 bar
- DR = dezincification resistance brass



Application information Uponor Wipex adapter S-Press PN6

Specification

- Wipex fittings in corrosion-resistant brass, dezincification based on EN ISO 6509 with stainless steel screw.
- O-ring sealing between Wipex coupling and base fitting connectors
- Bolt set for couplers include a hex socket bolt in stainless steel and the nut as well as washer from brass
- Pre-open sleeve design with assembled support part for the dimension 63-110mm.

Application



- Fittings for pipe systems Thermo, Aqua, Quattro, Supra, Supra PLUS and Supra Standard
- Connection of PE and PE-Xa medium pipe to couplers with cylindrical inch male thread
- Max. operating temperature 95°C

Certification

- Approvals should be checked by local responsible person

Uponor Wipex adapter S-Press PN6 40x3,7-40x4,0

1060059



Product code

Item no EAN	4021598121676
Item no GF	35001060059
Item no GTIN	04021598121676

Dimensions

Item Unit Height	82
Item Unit Length	61
Item Unit Weight	0,409
Item Unit Width	46
Item_UOM	pce

Measurements

LENGTH_L	79
Length (l1)	38
Length (l2)	30
z1	12

Packaging

Packaging GTIN PL1	06414905412402
Packaging GTIN PL3	06414905412419
Packaging Height PL1	84
Packaging Height PL3	155
Packaging Length PL1	63
Packaging Length PL3	272
Packaging Quantity PL1	1
Packaging Quantity PL3	15
Packaging Type PL1	Plastic_Bag
Packaging Type PL3	Box
Packaging Volume PL1	0,000254016
Packaging Volume PL3	0,01054

Packaging Weight PL1	0,417
Packaging Weight PL3	6,447
Packaging Width PL1	48
Packaging Width PL3	250

Documents

Page with all documents 

Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211

www.uponor.com