

Uponor Wipex adapter S-Press PN6 50x4,6-50x4,5

1060060

- Connection of PE-Xa pipe to Uponor MLC pipe.
- 6 bar
- DR = dezincification resistance brass



Application information Uponor Wipex adapter S-Press PN6

Specification

- Wipex fittings in corrosion-resistant brass, dezincification based on EN ISO 6509 with stainless steel screw.
- O-ring sealing between Wipex coupling and base fitting connectors
- Bolt set for couplers include a hex socket bolt in stainless steel and the nut as well as washer from brass
- Pre-open sleeve design with assembled support part for the dimension 63-110mm.

Application

- Fittings for pipe systems Thermo, Aqua, Quattro, Supra, Supra PLUS and Supra Standard
- Connection of PE and PE-Xa medium pipe to couplers with cylindrical inch male thread
- Max. operating temperature 95°C

Certification

- Approvals should be checked by local responsible person

Uponor Wipex adapter S-Press PN6 50x4,6-50x4,5

1060060



Product code

Item no EAN	4021598121683
Item no GF	35001060060
Item no GTIN	04021598121683

Dimensions

Item Unit Height	53
Item Unit Length	84
Item Unit Weight	0,652
Item Unit Width	70
Item_UOM	pce

Measurements

LENGTH_L	86
Length (l1)	38
Length (l2)	37
z1	12

Packaging

Packaging GTIN PL1	06414905412426
Packaging GTIN PL3	06414905412433
Packaging Height PL1	55
Packaging Height PL3	145
Packaging Length PL1	86
Packaging Length PL3	268
Packaging Quantity PL1	1
Packaging Quantity PL3	10
Packaging Type PL1	Plastic_Bag
Packaging Type PL3	Box
Packaging Volume PL1	0,00034056
Packaging Volume PL3	0,009715

Packaging Weight PL1	0,662
Packaging Weight PL3	6,7
Packaging Width PL1	72
Packaging Width PL3	250

Documents

Page with all documents 

Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211

www.uponor.com