Product data sheet



GF Uponor MLC deburring tool universal

1060167

- for MLC pipes



Application information GF Uponor MLC deburring tool universal

Specification

- Oxygen diffusion resistant multi-layer composite pipe(PE-RT - adhesive - longitudinally welded aluminium - adhesive - PE-RT)
- Fire classification E according to EN 13501-1.
- With pipe end caps as hygienic seal according EN 806.

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

GF Uponor MLC deburring tool universal

1060167



Product code

Item no EAN	4021598121843
Item no GF	35001060167
Item no GTIN	04021598121843
Item no LVI	1725999
Item no NOBB	47366442
Item no NRF	5110027
Item no RSK	1880653
Item no VVS	087393196

Dimensions

Item Unit Height	150
Item Unit Length	25
Item Unit Weight	0,03
Item Unit Width	25
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905464005
Packaging GTIN PL3	06414905449743
Packaging Height PL1	26
Packaging Height PL3	205
Packaging Length PL1	177
Packaging Length PL3	290
Packaging Material (number) PL1	20
Packaging Material (number) PL3	20
Packaging Material PL1	Corrugated fibreboard
Packaging Material PL3	Corrugated fibreboard
Packaging Material (short) PL1	PAP
Packaging Material (short) PL3	PAP
Packaging Quantity PL1	1
Packaging Quantity PL3	50

Packaging Type PL1	Base_Box
Packaging Type PL3	Box
Packaging Volume PL1	0,000119652
Packaging Volume PL3	0,00921475
Packaging Weight PL1	0,04
Packaging Weight PL3	2,05
Packaging Width PL1	26
Packaging Width PL3	155

Technical data

Recycling Text Block PL1	Corrugated fibreboard
Recycling Text Block PL3	Corrugated fibreboard

Documents

Page with all documents

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E communications@georgfischer.com

www.uponor.com

+GF+