

Uponor Vario PLUS insulation kit

1063207

- Insulation thickness 19 mm, 0,038 W/mK
- Length 665 mm
- Fire classification BL-s3,do (EN 13501-1)



Application information Uponor Vario PLUS insulation kit

Specification

- Modular fibre glass reinforced polyamide manifold with 1,3,4,6 loops for connection with basic kit
- connection right or left with flat sealing or connection from below with optional elbowset
- supply with lockshield (LS) valve for balancing with adjusting ring or supply with Flowmeter (FM) for balancing
- shut-off and flow view
- adjusting ring for balancing without tools
- prepared places for room name labels
- return with valves and caps, prepared for actuators
- loop connection G3/4" eurocone
- loop pitch 50 mm
- header pitch 225 mm

Actuator:

- NC (normally closed) = closes without power

Application

- for underfloor heating and cooling
- can be combined with actuators MT 30x1,5

Certification

- CE

Uponor Vario PLUS insulation kit

1063207



Product code

| | |
|--------------|----------------|
| Item no EAN | 4021598124400 |
| Item no GF | 35001063207 |
| Item no GTIN | 04021598124400 |
| Item no RSK | 2419859 |
| Item no VVS | 087604200 |

Dimensions

| | |
|------------------|------|
| Item Unit Height | 55 |
| Item Unit Length | 655 |
| Item Unit Weight | 0,32 |
| Item Unit Width | 190 |
| Item_UOM | set |

Packaging

| | |
|------------------------|----------------|
| Packaging GTIN PL3 | 06414905450404 |
| Packaging Height PL3 | 200 |
| Packaging Length PL3 | 800 |
| Packaging Quantity PL3 | 1 |
| Packaging Type PL3 | Box |
| Packaging Volume PL3 | 0,128 |
| Packaging Weight PL3 | 0,323 |
| Packaging Width PL3 | 800 |

Documents

Page with all documents

Finland

T +358 (0)20 129 211

www.uponor.com