


Uponor S-Press PLUS adapter female thread 16-Rp1/2"FT

1070515

- Made of tin-plated DR brass



Application information Uponor S-Press PLUS adapter female thread

Specification

- Unique press indicator
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access
- Colour code
- Fixed press sleeve with inspection window
- Precise jaw fixation
- Fast diameter recognition
- Accurate test safety function
- 100% backward compatible with existing Uponor components
- Flow rate optimized fitting body

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

if not different mentioned:

- Male and female threads acc.to EN 10226-1.

Certification


- Approvals by local OM.

E.g.

- DVGW
- AENOR

Uponor S-Press PLUS adapter female thread 16-Rp1/2"FT

1070515



Measurements

Female thread Rp	1/2
LENGTH_L	46,5
Length (l1)	15
Length (l2)	19,8
z1	11,7

Product code

Item no EAN	6414905218356
Item no GF	35001070515
Item no GTIN	06414905218356
Item no LVI	1720181
Item no NOBB	55171862
Item no NRF	5114441
Item no RSK	1899420
Item no VVS	045482189

Dimensions

Item Unit Height	30.5
Item Unit Length	46.5
Item Unit Weight	0,073
Item Unit Width	27
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905634958
Packaging GTIN PL3	06414905424078
Packaging GTIN PL4	06414905499243
Packaging Height PL1	89
Packaging Height PL3	95
Packaging Height PL4	714

Packaging Length PL1	176
Packaging Length PL3	277
Packaging Length PL4	1200
Packaging Quantity PL1	20
Packaging Quantity PL3	80
Packaging Quantity PL4	7680
Packaging Type PL1	Base_Box
Packaging Type PL3	Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,001049488
Packaging Volume PL3	0,004710385
Packaging Volume PL4	0,68544
Packaging Weight PL1	1,498
Packaging Weight PL3	6,192
Packaging Weight PL4	619,432
Packaging Width PL1	67
Packaging Width PL3	179
Packaging Width PL4	800

Documents

Page with all documents



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211

www.uponor.com