Product data sheet





GF Uponor S-Press PLUS elbow 90° 25-25

1070525

- Made of tin-plated DR brass (lead-free)







Application information GF Uponor S-Press PLUS elbow 90°

Specification

- Unique press indicator
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access
- Colour code
- Fixed press sleeve with insprection window
- Precise jaw fixation
- Fast diameter recognition
- Accurate test safety function
- 100% backward compatible with existing Uponor components
- Flow rate optimized fitting body

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

if not different mentioned:
- Male and female threads acc.to EN 10226-1.


Certification


- Approvals by local OM.
E.g.
- DVGW
- AENOR

GF Uponor S-Press PLUS elbow 90° 25-25

1070525







Product code

Item no EAN	6414905218455
Item no GF	35001070525
Item no GTIN	06414905218455
Item no LVI	1720191
Item no NOBB	55171964
Item no NRF	5114452
Item no RSK	1896531
Item no VVS	045470125

Dimensions

Item Unit Height	62.8
Item Unit Length	62.8
Item Unit Weight	0,155
Item Unit Width	32.3
Item_UOM	pce

Measurements

Length (l1)	47
Length (l2)	47
z1	19
Z2	19

Packaging

Packaging GTIN PL1	06414905290178
Packaging GTIN PL3	06414905424184
Packaging GTIN PL4	06414905290192
Packaging Height PL1	89
Packaging Height PL3	188

Packaging Height PL4	708
Packaging Length PL1	176
Packaging Length PL3	277
Packaging Length PL4	1200
Packaging Quantity PL1	5
Packaging Quantity PL3	40
Packaging Quantity PL4	1920
Packaging Type PL1	Base_Box
Packaging Type PL3	Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,001049488
Packaging Volume PL3	0,009321604
Packaging Volume PL4	0,67968
Packaging Weight PL1	0,812
Packaging Weight PL3	6,756
Packaging Weight PL4	343,2
Packaging Width PL1	67
Packaging Width PL3	179
Packaging Width PL4	800

Documents

Page with all documents

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E communications@georgfischer.com

www.uponor.com

+GF+