
Product data sheet



GF Uponor S-Press PLUS coupling 16-16

1070547

- Made of tin-plated DR brass (lead-free)



Application information GF Uponor S-Press PLUS coupling

Specification

- Unique press indicator
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access
- Colour code
- Fixed press sleeve with insprection window
- Precise jaw fixation
- Fast diameter recognition
- Accurate test safety function
- 100% backward compatible with existing Uponor components
- Flow rate optimized fitting body

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.


if not different mentioned:
- Male and female threads acc.to EN 10226-1.

Certification

- Approvals by local OM.
E.g.
- DVGW
- AENOR

GF Uponor S-Press PLUS coupling 16-16

1070547



Product code

Item no EAN	6414905218677
Item no GF	35001070547
Item no GTIN	06414905218677
Item no LVI	1720735
Item no NOBB	55172180
Item no NRF	5114476
Item no RSK	1899428
Item no VVS	045480016

Dimensions

Item Unit Height	21.9
Item Unit Length	51.2
Item Unit Weight	0,039
Item Unit Width	21.9
Item_UOM	pce

Measurements

LENGTH_L	51,2
Length (l1)	19,8
Length (l2)	19,8
z1	11,6

Packaging

Packaging GTIN PL1	06414905634996
Packaging GTIN PL3	06414905424351
Packaging GTIN PL4	06414905499427
Packaging Height PL1	89
Packaging Height PL3	95

Packaging Height PL4	714
Packaging Length PL1	176
Packaging Length PL3	277
Packaging Length PL4	1200
Packaging Quantity PL1	20
Packaging Quantity PL3	80
Packaging Quantity PL4	7680
Packaging Type PL1	Base_Box
Packaging Type PL3	Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,001049488
Packaging Volume PL3	0,004710385
Packaging Volume PL4	0,68544
Packaging Weight PL1	0,818
Packaging Weight PL3	3,472
Packaging Weight PL4	358,312
Packaging Width PL1	67
Packaging Width PL3	179
Packaging Width PL4	800

Documents

Page with all documents

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E communications@georgfischer.com

www.uponor.com

+GF+