


Uponor S-Press PLUS reducer 25-20

1070554

- Made of tin-plated DR brass



Application information Uponor S-Press PLUS reducer

Specification

- Unique press indicator
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access
- Colour code
- Fixed press sleeve with inspection window
- Precise jaw fixation
- Fast diameter recognition
- Accurate test safety function
- 100% backward compatible with existing Uponor components
- Flow rate optimized fitting body

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

if not different mentioned:

- Male and female threads acc.to EN 10226-1.

Certification


- Approvals by local OM.

E.g.

- DVGW
- AENOR

Uponor S-Press PLUS reducer 25-20

1070554



Product code

Item no EAN	6414905218745
Item no GF	35001070554
Item no GTIN	06414905218745
Item no LVI	1720741
Item no NOBB	55172244
Item no NRF	5114483
Item no RSK	1899434
Item no VVS	045480308

Dimensions

Item Unit Height	32.3
Item Unit Length	61.2
Item Unit Weight	0,089
Item Unit Width	32.3
Item_UOM	pce

Measurements

LENGTH_L	61,2
Length (l1)	28,3
Length (l2)	21,3
z1	11,6

Packaging

Packaging GTIN PL1	06414905635313
Packaging GTIN PL3	06414905635498
Packaging GTIN PL4	06414905499489
Packaging Height PL1	89
Packaging Height PL3	188
Packaging Height PL4	708
Packaging Length PL1	176

Packaging Length PL3	277
Packaging Length PL4	1200
Packaging Quantity PL1	10
Packaging Quantity PL3	80
Packaging Quantity PL4	3840
Packaging Type PL1	Base_Box
Packaging Type PL3	Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,001049488
Packaging Volume PL3	0,009321604
Packaging Volume PL4	0,67968
Packaging Weight PL1	0,928
Packaging Weight PL3	7,824
Packaging Weight PL4	400,552
Packaging Width PL1	67
Packaging Width PL3	179
Packaging Width PL4	800

Documents

Page with all documents



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211

www.uponor.com