


## Uponor S-Press PLUS reducer 32-20

1070555

- Made of tin-plated DR brass



### Application information Uponor S-Press PLUS reducer

#### Specification

- Unique press indicator
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access
- Colour code
- Fixed press sleeve with inspection window
- Precise jaw fixation
- Fast diameter recognition
- Accurate test safety function
- 100% backward compatible with existing Uponor components
- Flow rate optimized fitting body

#### Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

if not different mentioned:

- Male and female threads acc.to EN 10226-1.

#### Certification


- Approvals by local OM.

E.g.

- DVGW
- AENOR

## Uponor S-Press PLUS reducer 32-20

1070555



### Product code

Item no EAN	6414905218752
Item no GF	35001070555
Item no GTIN	06414905218752
Item no LVI	1720742
Item no NOBB	55172252
Item no NRF	5114484
Item no RSK	1899435
Item no VVS	045480367

### Dimensions

Item Unit Height	39.3
Item Unit Length	61.2
Item Unit Weight	0,12
Item Unit Width	39.3
Item_UOM	pce

### Measurements

LENGTH_L	61,2
Length (l1)	28,3
Length (l2)	21,3
z1	11,6

### Packaging

Packaging GTIN PL1	06414905635320
Packaging GTIN PL3	06414905635504
Packaging GTIN PL4	06414905499496
Packaging Height PL1	89
Packaging Height PL3	189
Packaging Height PL4	711
Packaging Length PL1	176

Packaging Length PL3	357
Packaging Length PL4	1200
Packaging Quantity PL1	10
Packaging Quantity PL3	80
Packaging Quantity PL4	1920
Packaging Type PL1	Base_Box
Packaging Type PL3	Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00211464
Packaging Volume PL3	0,018555075
Packaging Volume PL4	0,68256
Packaging Weight PL1	1,274
Packaging Weight PL3	10,712
Packaging Weight PL4	282,088
Packaging Width PL1	135
Packaging Width PL3	275
Packaging Width PL4	800

## Documents

Page with all documents



### Uponor Corporation

Ilmalantori 4  
00240, Helsinki  
Finland

T +358 (0)20 129 211

[www.uponor.com](http://www.uponor.com)