Product data sheet





GF Uponor S-Press PLUS tee reducer 20-25-16

1070570

- Made of tin-plated DR brass (lead-free)







Application information GF Uponor S-Press PLUS tee reducer

Specification

- Unique press indicator
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access
- Colour code
- Fixed press sleeve with insprection window
- Precise jaw fixation
- Fast diameter recognition
- Accurate test safety function
- 100% backward compatible with existing Uponor components
- Flow rate optimized fitting body

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

if not different mentioned:
- Male and female threads acc.to EN 10226-1.


Certification


- Approvals by local OM.
E.g.
- DVGW
- AENOR

GF Uponor S-Press PLUS tee reducer 20-25-16

1070570







Product code

Item no EAN	6414905218905
Item no GF	35001070570
Item no GTIN	06414905218905
Item no LVI	1720752
Item no NOBB	55172354
Item no NRF	5114495
Item no RSK	1808014
Item no VVS	045476290

Dimensions

Item Unit Height	60.2
Item Unit Length	78
Item Unit Weight	0,167
Item Unit Width	32.3
Item_UOM	pce

Measurements

Length (l1)	39,8
Length (l2)	46,8
Length (l3)	38,3
z1	18,5
Z2	18,5
Z3	18,5

Packaging

Packaging GTIN PL1	06414905296071
Packaging GTIN PL3	06414905424528
Packaging GTIN PL4	06414905296088

Packaging Height PL1	89
Packaging Height PL3	188
Packaging Height PL4	708
Packaging Length PL1	176
Packaging Length PL3	277
Packaging Length PL4	1200
Packaging Quantity PL1	10
Packaging Quantity PL3	40
Packaging Quantity PL4	1920
Packaging Type PL1	Base_Box
Packaging Type PL3	Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00211464
Packaging Volume PL3	0,009321604
Packaging Volume PL4	0,67968
Packaging Weight PL1	1,709
Packaging Weight PL3	7,096
Packaging Weight PL4	366,24
Packaging Width PL1	135
Packaging Width PL3	179
Packaging Width PL4	800

Documents

Page with all documents

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E communications@georgfischer.com

www.uponor.com

+GF+