


Uponor S-Press PLUS tee reducer 25-16-20

1070573

- Made of tin-plated DR brass



Application information Uponor S-Press PLUS tee reducer

Specification

- Unique press indicator
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access
- Colour code
- Fixed press sleeve with inspection window
- Precise jaw fixation
- Fast diameter recognition
- Accurate test safety function
- 100% backward compatible with existing Uponor components
- Flow rate optimized fitting body

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

if not different mentioned:

- Male and female threads acc.to EN 10226-1.

Certification


- Approvals by local OM.

E.g.

- DVGW
- AENOR

Uponor S-Press PLUS tee reducer 25-16-20

1070573



Product code

Item no EAN	6414905218936
Item no GF	35001070573
Item no GTIN	06414905218936
Item no LVI	1720755
Item no NOBB	55172384
Item no NRF	5114498
Item no RSK	1808017
Item no VVS	045476325

Dimensions

Item Unit Height	54.3
Item Unit Length	82
Item Unit Weight	0,144
Item Unit Width	32.3
Item_UOM	pce

Measurements

Length (I1)	44,3
Length (I2)	38,3
Length (I3)	37,8
z1	16
Z2	18,5
Z3	16,5

Packaging

Packaging GTIN PL1	06414905295838
Packaging GTIN PL3	06414905424559
Packaging GTIN PL4	06414905295845
Packaging Height PL1	89
Packaging Height PL3	188

Packaging Height PL4	708
Packaging Length PL1	176
Packaging Length PL3	277
Packaging Length PL4	1200
Packaging Quantity PL1	5
Packaging Quantity PL3	40
Packaging Quantity PL4	1920
Packaging Type PL1	Base_Box
Packaging Type PL3	Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,001049488
Packaging Volume PL3	0,009321604
Packaging Volume PL4	0,67968
Packaging Weight PL1	0,757
Packaging Weight PL3	6,316
Packaging Weight PL4	322,08
Packaging Width PL1	67
Packaging Width PL3	179
Packaging Width PL4	800

Documents

Page with all documents 

Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211

www.uponor.com