


## Uponor S-Press PLUS tee female thread 32-Rp1/2"FT-32

1070600

- Made of tin-plated DR brass



### Application information Uponor S-Press PLUS tee female thread

#### Specification

- Unique press indicator
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access
- Colour code
- Fixed press sleeve with inspection window
- Precise jaw fixation
- Fast diameter recognition
- Accurate test safety function
- 100% backward compatible with existing Uponor components
- Flow rate optimized fitting body

#### Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

if not different mentioned:

- Male and female threads acc.to EN 10226-1.

#### Certification


- Approvals by local OM.

E.g.

- DVGW
- AENOR

## Uponor S-Press PLUS tee female thread 32-Rp1/2"FT-32

1070600



### Measurements

Female thread Rp	1/2
Length (l1)	46,5
Length (l2)	40,3
Length (l3)	46,5
z1	18,2
Z2	25,3
Z3	18,2

### Product code

Item no EAN	6414905219209
Item no GF	35001070600
Item no GTIN	06414905219209
Item no LVI	1720774
Item no NOBB	55172577
Item no NRF	5114519
Item no RSK	1808036
Item no VVS	045478365

### Dimensions

Item Unit Height	59.8
Item Unit Length	93
Item Unit Weight	0,261
Item Unit Width	39.3
Item_UOM	pce

### Packaging

Packaging GTIN PL1	06414905468638
Packaging GTIN PL3	06414905424740
Packaging GTIN PL4	06414905499564
Packaging Height PL1	89

Packaging Height PL3	188
Packaging Height PL4	708
Packaging Length PL1	176
Packaging Length PL3	277
Packaging Length PL4	1200
Packaging Quantity PL1	5
Packaging Quantity PL3	20
Packaging Quantity PL4	960
Packaging Type PL1	Base_Box
Packaging Type PL3	Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00211464
Packaging Volume PL3	0,009321604
Packaging Volume PL4	0,67968
Packaging Weight PL1	1,344
Packaging Weight PL3	5,636
Packaging Weight PL4	296,16
Packaging Width PL1	135
Packaging Width PL3	179
Packaging Width PL4	800

## Documents

Page with all documents



### Uponor Corporation

Ilmalantori 4  
00240, Helsinki  
Finland

T +358 (0)20 129 211

[www.uponor.com](http://www.uponor.com)