


Uponor S-Press PLUS adapter 25-22CU

1070618

- Made of tin-plated brass



Application information Uponor S-Press PLUS adapter

Specification

- Unique press indicator
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access
- Colour code
- Fixed press sleeve with inspection window
- Precise jaw fixation
- Fast diameter recognition
- Accurate test safety function
- 100% backward compatible with existing Uponor components
- Flow rate optimized fitting body

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

if not different mentioned:

- Male and female threads acc.to EN 10226-1.

Certification


- Approvals by local OM.

E.g.

- DVGW
- AENOR

Uponor S-Press PLUS adapter 25-22CU

1070618



Product code

Item no EAN	6414905219384
Item no GF	35001070618
Item no GTIN	06414905219384
Item no LVI	1720792
Item no NOBB	55172755
Item no NRF	5114539
Item no RSK	1899443
Item no VVS	045313022

Dimensions

Item Unit Height	32.3
Item Unit Length	88
Item Unit Weight	0,1
Item Unit Width	32.3
Item_UOM	pce

Measurements

LENGTH_L	88
Length (l1)	41
Length (l2)	28,3
z1	18,7

Packaging

Packaging GTIN PL1	06414905468782
Packaging GTIN PL3	06414905424795
Packaging GTIN PL4	06414905499717
Packaging Height PL1	89
Packaging Height PL3	95
Packaging Height PL4	714
Packaging Length PL1	176

Packaging Length PL3	277
Packaging Length PL4	1200
Packaging Quantity PL1	5
Packaging Quantity PL3	20
Packaging Quantity PL4	1920
Packaging Type PL1	Base_Box
Packaging Type PL3	Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,001049488
Packaging Volume PL3	0,004710385
Packaging Volume PL4	0,68544
Packaging Weight PL1	0,537
Packaging Weight PL3	2,348
Packaging Weight PL4	240,96
Packaging Width PL1	67
Packaging Width PL3	179
Packaging Width PL4	800

Documents

Page with all documents



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211

www.uponor.com