


## Uponor S-Press PLUS adapter 32-28CU

1070620

- Made of tin-plated brass



### Application information Uponor S-Press PLUS adapter

#### Specification

- Unique press indicator
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access
- Colour code
- Fixed press sleeve with inspection window
- Precise jaw fixation
- Fast diameter recognition
- Accurate test safety function
- 100% backward compatible with existing Uponor components
- Flow rate optimized fitting body

#### Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

if not different mentioned:


- Male and female threads acc.to EN 10226-1.

#### Certification

- Approvals by local OM.
- E.g.
- DVGW
  - AENOR

## Uponor S-Press PLUS adapter 32-28CU

1070620



### Product code

Item no EAN	6414905219407
Item no GF	35001070620
Item no GTIN	06414905219407
Item no LVI	1720794
Item no NOBB	55172766
Item no NRF	5114542
Item no RSK	1899445
Item no VVS	045485032

### Dimensions

Item Unit Height	39.3
Item Unit Length	92
Item Unit Weight	0,16
Item Unit Width	39.3
Item_UOM	pce

### Measurements

LENGTH_L	92
Length (l1)	43
Length (l2)	28,3
z1	20,7

### Packaging

Packaging GTIN PL1	06414905468805
Packaging GTIN PL3	06414905424801
Packaging GTIN PL4	06414905499731
Packaging Height PL1	89
Packaging Height PL3	188
Packaging Height PL4	708
Packaging Length PL1	176

Packaging Length PL3	277
Packaging Length PL4	1200
Packaging Quantity PL1	5
Packaging Quantity PL3	20
Packaging Quantity PL4	960
Packaging Type PL1	Base_Box
Packaging Type PL3	Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00211464
Packaging Volume PL3	0,009321604
Packaging Volume PL4	0,67968
Packaging Weight PL1	0,839
Packaging Weight PL3	3,616
Packaging Weight PL4	199,2
Packaging Width PL1	135
Packaging Width PL3	179
Packaging Width PL4	800

## Documents

Page with all documents



### Uponor Corporation

Ilmalantori 4  
00240, Helsinki  
Finland

T +358 (0)20 129 211

[www.uponor.com](http://www.uponor.com)