


Uponor S-Press PLUS U-tap elbow 25-Rp1/2"FT-25

1070633

- For on wall installation or attachment with rotation protection to the Uponor Smart Aqua mounting angles and plates.



Application information Uponor S-Press PLUS U-tap elbow

Specification

- Unique press indicator
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access
- Colour code
- Fixed press sleeve with inspection window
- Precise jaw fixation
- Fast diameter recognition
- Accurate test safety function
- 100% backward compatible with existing Uponor components
- Flow rate optimized fitting body

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

if not different mentioned:


- Male and female threads acc.to EN 10226-1.

Certification

- Approvals by local OM.
- E.g.
- DVGW
 - AENOR

Uponor S-Press PLUS U-tap elbow 25-Rp1/2"FT-25

1070633



Measurements

Female thread Rp	1/2
Length (l1)	64
Length (l2)	64
Length (l3)	27
Z Measurement b	60
Z Measurement k	40
z1	35,7
Z2	35,7
Z4	9

Product code

Item no EAN	6414905219490
Item no GF	35001070633
Item no GTIN	06414905219490

Dimensions

Item Unit Height	51
Item Unit Length	90
Item Unit Weight	0,368
Item Unit Width	92.1
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905468898
Packaging GTIN PL4	06414905499823
Packaging Height PL1	89
Packaging Height PL4	678
Packaging Length PL1	176
Packaging Length PL4	1200
Packaging Quantity PL1	3

Packaging Quantity PL4	576
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00211464
Packaging Volume PL4	0,65088
Packaging Weight PL1	1,184
Packaging Weight PL4	251,328
Packaging Width PL1	135
Packaging Width PL4	800

Documents

Page with all documents



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211

www.uponor.com