


## Uponor S-Press PLUS adapter wall penetr. 16-G1/2"FT

**1070652**

- For lead-through through walls.
- Dimensions of attachment plate (H x W x D) 100 x 50 x 2 mm.
- Hole circle diameter 33 mm.



### Application information Uponor S-Press PLUS adapter wall penetr.

#### Specification

- Unique press indicator
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access
- Colour code
- Fixed press sleeve with inspection window
- Precise jaw fixation
- Fast diameter recognition
- Accurate test safety function
- 100% backward compatible with existing Uponor components
- Flow rate optimized fitting body

#### Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

if not different mentioned:

- Male and female threads acc.to EN 10226-1.

#### Certification


- Approvals by local OM.

E.g.

- DVGW
- AENOR

## Uponor S-Press PLUS adapter wall penetr. 16-G1/2"FT

1070652



### Measurements

Female thread Rp	0,5
LENGTH_L	50,5
Length (l1)	17
Length (l2)	19,8
Length (l3)	100
Wall thickness_s	2
Z Measurement k	40
z1	13,7

### Product code

Item no EAN	6414905219681
Item no GF	35001070652
Item no GTIN	06414905219681
Item no NRF	5071608

### Dimensions

Item Unit Height	52.2
Item Unit Length	100
Item Unit Weight	0,14
Item Unit Width	50.5
Item_UOM	pce

### Packaging

Packaging GTIN PL1	06414905468959
Packaging GTIN PL2	06414905442850
Packaging GTIN PL4	06414905499878
Packaging Height PL1	57
Packaging Height PL2	89
Packaging Height PL4	678
Packaging Length PL1	105

Packaging Length PL2	176
Packaging Length PL4	1200
Packaging Quantity PL1	1
Packaging Quantity PL2	5
Packaging Quantity PL4	960
Packaging Type PL1	Plastic_Bag
Packaging Type PL2	Medium_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00033516
Packaging Volume PL2	0,00211464
Packaging Volume PL4	0,65088
Packaging Weight PL1	0,141
Packaging Weight PL2	0,739
Packaging Weight PL4	174,72
Packaging Width PL1	56
Packaging Width PL2	135
Packaging Width PL4	800

## Documents

Page with all documents



### Uponor Corporation

Ilmalantori 4  
00240, Helsinki  
Finland

T +358 (0)20 129 211

[www.uponor.com](http://www.uponor.com)