


Uponor Ecoflex elbow Rp4-Rp4

1078366

- Thread Rp", hemp sealing
- 6 bar, SDR 11 / 10 bar, SDR 7,4
- DR = dezincification resistance brass



Application information Uponor Ecoflex elbow

Specification

- Wipex fittings in corrosion-resistant brass, dezincification based on EN ISO 6509 with stainless steel screw.
- O-ring sealing between Wipex coupling and base fitting connectors
- Bolt set for couplers include a hex socket bolt in stainless steel and the nut as well as washer from brass
- Pre-open sleeve design with assembled support part for the dimension 63-110mm.

Application


- Fittings for pipe systems Thermo, Aqua, Quattro, Supra, Supra PLUS and Supra Standard
- Connection of PE and PE-Xa medium pipe to couplers with cylindrical inch male thread
- Max. operating temperature 95°C

Certification

- Approvals should be checked by local responsible person

Uponor Ecoflex elbow Rp4-Rp4

1078366



Measurements

Female thread Rp	4
Length (l1)	92
Length (l2)	92

Product code

Item no EAN	4021598130258
Item no GF	35001078366
Item no GTIN	04021598130258
Item no LVI	1938511
Item no NOBB	49606934
Item no NRF	8361338
Item no RSK	2282486
Item no VVS	087832016

Dimensions

Item Unit Height	127
Item Unit Length	150
Item Unit Weight	2,65
Item Unit Width	155
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414900328289
Packaging Height PL1	155
Packaging Length PL1	290
Packaging Quantity PL1	1
Packaging Type PL1	Base_Box
Packaging Volume PL1	0,00899
Packaging Weight PL1	2,76
Packaging Width PL1	200

Documents

Page with all documents



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E
communications@georgfischer.
com