Product data sheet



GF Uponor S-Press battery charger Mini2, UP110

1083610

- Quick-charger for 18V Li-Ion batteries, 230 V
- Charging time: 1.3 Ah 15 min,
- 3.0 Ah 22 min
- Mains supply: 230 V AC
- Voltage range: 18 V
- Weight: 1,0 kg





Application information GF Uponor S-Press battery charger

Specification

- with fixed press sleeve
- stop ring
- test safety

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.

- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

- if not different mentioned:
Male and female threads acc.to EN 10226-1.

GF Uponor S-Press battery charger Mini2, UP110

1083610





Product code

Item no EAN	4021598131828
Item no GF	35001083610
Item no GTIN	04021598131828
Item no LVI	1725912
Item no NOBB	48959657
Item no NRF	5071297
Item no RSK	1881876
Item no VVS	045498465

Dimensions

Item Unit Height	110
Item Unit Length	155
Item Unit Weight	0,829
Item Unit Width	180
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905469765
Packaging Height PL1	168
Packaging Length PL1	235
Packaging Quantity PL1	1
Packaging Type PL1	Base_Box
Packaging Volume PL1	0,0073038
Packaging Weight PL1	1,149
Packaging Width PL1	185

Documents

Page with all documents

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E communications@georgfischer.com

www.uponor.com

+GF+