

Uponor Ecoflex Quattro Pipe 2x32x2,9-25x3,5-20x2,8/175

1084888

- Heating and warm tap water with circulation
- Four medium pipe PE-Xa, SDR 11 and 7,4
- Max. load 6 bar heating / 10 bar tap water / 95°C
- PEX foam, HDPE casing
- Coloured centre profil to avoid confusion between the lines



Application information Uponor Ecoflex Quattro Pipe

Specification

- Flexible, pre-insulated, self-compensating plastic pipe system
- Medium pipe: Cross-linked polyethylene (PE-Xa) pipe based on EN ISO 15875, natural coloured, PN 6 (SDR 11) and PN10 (SDR 7,4), Oxygen tightness based on EN 15632 for heating pipes
- Insulating material: closed-cell PE-X foam, permanently elastic, ageing-resistant
- Casing pipe: Corrugated polyethylene (HDPE)

Application

- Transport of heating and warm tap water for buried installations.
- Heating operating temperature 80°C based on EN 15632
- Tap water operating temperature 70°C based on EN ISO 15875
- Malfunction temperature 95°C
- Static verification for heavy traffic load of 60 tons

Certification

- Approvals should be checked by local responsible person

Uponor Ecoflex Quattro Pipe 2x32x2,9-25x3,5-20x2,8/175

1084888



Measurements

Bending radius M	0,8
Outer Diameter_do	175
Outer Diameter_do1	32
Outer Diameter_do2	25
Outer Diameter_do3	20
Wall thickness_s1	2,9
Wall thickness_s2	3,5
Wall thickness_s3	2,8

Product code

Item no EAN	4021598133174
Item no GF	35001084888
Item no GTIN	04021598133174
Item no LVI	3010341
Item no NRF	8360877
Item no RSK	2266165
Item no VVS	087817732

Dimensions

Item Unit Height	175
Item Unit Length	1000
Item Unit Weight	2,75
Item Unit Width	175
Item_UOM	m

Packaging

Packaging GTIN PL1	06414905283514
Packaging Height PL1	2400
Packaging Length PL1	1850
Packaging Quantity PL1	200

Packaging Type PL1	Coil
Packaging Volume PL1	10,656
Packaging Weight PL1	550
Packaging Width PL1	2400

Documents

Page with all documents 

Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E
communications@georgfischer.
com